## AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A system for testing devices, said system comprising:

a first device for test;

a second device for test coupled to said first device in a scan chain; and

a signal selector coupled between said first and second devices, said

signal selector for selecting between an output signal that is output from said first

device and a bypass signal that has bypassed said first device; and

, said selecting depending on whether said signal selector detects power

in a first power rail that supplies power soupled to said first device and is coupled

to said signal selector, wherein said signal selector selects said output signal

when said first device is powered on and said bypass signal when said first

device is not powered on.

2-3. (Canceled).

4. (Previously Presented) The system of Claim 1 wherein said signal

selector is coupled to a standby power rail that powers said signal selector.

5. (Canceled).

6. (Original) The system of Claim 1 wherein said second device is

coupled to a second power rail.

7. (Original) The system of Claim 1 wherein said signal selector is a

multiplexer.

200209360-1 Examiner: CHUNG, P.

Serial No.: 10/607,159 Group Art Unit: 2138

2

8. (Original) The system of Claim 1 wherein said first and second devices

are boundary scan compliant devices.

9. (Currently Amended) A method of testing devices in a scan chain, said

method comprising:

selecting a bypass signal that has bypassed a first device;

selecting an output signal instead of said bypass signal, said output signal

being output from said first device, wherein said output signal is selected when

power is detected in a first power rail coupled to said first device and wherein

otherwise said bypass signal is selected when no power is detected in said first

power rail; and

forwarding a selected signal to a second device in said scan chain.

10. (Previously Presented) The method of Claim 9 wherein said selecting

between said bypass signal and said output signal is performed by a signal

selector that is coupled to said first power rail.

11. (Canceled).

12. (Original) The method of Claim 10 wherein said signal selector is

also coupled to a standby power rail.

13. (Canceled).

14. (Original) The method of Claim 9 wherein said first and second devices are boundary scan compliant devices.

15. (Currently Amended) A system for testing devices, said system comprising:

a first device for test coupled in a scan chain, said first device coupled to a first power rail;

an input line that delivers an input signal coupled to said first device; an output line coupled to said first device;

a bypass line coupled to said input line upstream of said first device; and a signal selector coupled to said output line and to said bypass line and also coupled to said first power rail; and

a bypass line coupled to said input line upstream of said first device and to said signal selector such that said input signal is delivered to said signal selector selector even if said first device is powered off, wherein said signal selector selects between a an output signal on said output line and a an input signal on delivered to said signal selector via said bypass line, depending on whether said signal selector detects power in said first power rail, wherein said output signal on said output line is selected when power is detected in said first power rail and otherwise said input signal on said bypass line is selected when no power is detected in said first power rail.

16-17. (Canceled).

18. (Previously Presented) The system of Claim 15 wherein said signal selector is also coupled to a standby power rail that powers said signal selector.

200209360-1 Examiner: CHUNG, P. 19. (Canceled).

20. (Original) The system of Claim 15 further comprising:

a second device for test coupled to said signal selector.

21. (Original) The system of Claim 20 wherein said first device is coupled

to one power rail and wherein said second device is coupled to a different power

rail.

22. (Original) The system of Claim 15 wherein said signal selector is a

multiplexer.

23. (Original) The system of Claim 15 wherein said first device is

boundary scan compliant.

200209360-1 Examiner: CHUNG, P.